## Now Hinged for Easy Install & Adjustment Pelco's Astro-Brac Triton

Astro-Brac Triton now features a hinged saddle clamp and includes three cables for *50% increased holding strength* over two cable brackets.

Astro-Brac Triton high tensile aluminum alloy clamp kits add strength with maximum adjustability and complete clamping versatility. They install easily with one tool and come complete with all necessary attaching hardware.

Features 600 ft. lbs. of rotational resistance. That's a **50% increase** over typical two cable brackets.



One tool for easy install and adjustability



ire ige



The hinged saddle clamp attaches any 1-1/2" (1.9" OD) diameter pipe/ tube

AB-3050

**Triton Hinged** 

for 1-1/2" Tube

Available in cable mount only

Corrosion

resistant material



Minimum breaking strength: Stainless cable - 3700 lbs. Fits supporting structure between 4-1/2" to 22".

> Accommodates (3) 3/16" stainless steel cables

Rotates 360° around the supporting arm or pole



**360**°

Rotates 75° in either the vertical or horizontal mounting



320 W. 18th St. • Edmond, OK 73013 • 405.340.3434 • Fax 405.340.3435 • pelcoinc.com • e-mail: sales@pelcoinc.com

## **Pelco's Astro-Brac Triton Series**

**360°** 

Plus additional adjustability with

tube saddle

360°

Plus additional adjustability with tube saddle

60

75'

## **Mounting Applications:**

Cameras, Signs, Sensors, Antennas and Special Equipment

## **Key Features:**

- 3 axis adjustability
- Stainless steel hardware
- Minimal standard tools to install/adjust
- Allows for through wiring of two (2) 5/8" diameter conductors
- Has 3 bands or cables for supporting added load

15 FE

0

- AB-3050 is designed to be used with 1-1/2" (1.9" OD) diameter tube
- AB-3040 and AB 3039 are designed to be used with 2-3/8" diameter tube
  New captured bearing washer design to prevent rotation on cable

Allows equipment to mount up to 15' above mast arm



320 W. 18th St. • Edmond, OK 73013 • 405.340.3434 • Fax 405.340.3435 • pelcoinc.com

**AB-3039** 

**AB-3050** 

**AB-3040**